

ATF SUPER III

**German Quality**

MUXX OIL GmbH
15 Frankenhauer St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- ATF SUPER III is an automatic transmission fluid blended from high quality mineral oil with a specifically balanced additive combination to provide high oxidation stability with excellent foam resistance, corrosion and wear friction additive to provide the smooth lock up of clutches without chatter.
- ATF SUPER III is developed with GM D-III additive package with outstanding mineral base stock which could be using on most type of transmission which GM D-III specification requirement.

Performance Levels

DEXRON III F/G/H Allison C4 CAT TO-2 MAN 339 Z1/Z2 MAN 339 V1/V2
 MB 236.10/236.9/236.7/236.5/236.1 Voith 55.6335 Voith 55.6336 Volvo 97341
 Mercon ZF 02F/03D/04D ZF 11A/11B/14B/16L

Test Item	Typical Spec.	Typical Result
Density @15°C	kg/m ³	868
Kin. Viscosity @40°C	mm ² /s	38.95
Kin. Viscosity @100°C	mm ² /s	7.33
Viscosity Index		160
Brookfield Viscosity@ -40°C	cP	35000
Flash Point COC	°C	210
Pour Point	°C	-33
Color		Red

*The Above Test Result is subject for change and for reference only

**EELQMS**EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM