



Coolant G11



German Quality

MUXX OIL GmbH
15 Frankenhäuser St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

-Coolant G11 50/50 is a long life silicate-containing nitrites, amines and phosphate free ready to use coolant in ethylene glycol to be used as a cooling and heat transferring fluid in combustion engines.

-Coolant G11 50/50 is based on ethylene glycol in combination with a power full additive technology to obtain the following properties.

- Extended life.
- Environmentally friendly.
- Reliability
- Excellent cavitation protection.
- Improved

Performance Levels

VW TL 774C MB 325.2 FIAT 9.55523 IVECO 18-1830 Ford ESD M97B49
GM GME L 1301 GM 6901599 MAN 324 NF MTU MTL 5048
Volvo Construction BS 6580 JASO M325

Test Item	Typical Spec.	Typical Result
Colour		Orange
Density @15°C	kg/l	1.07
Equilibrium Boiling Point	°C	125
Reserve Alkalinity (pH 5.5)		8
pH @ 20°C		7.2
Refractive Index, 20°C		1.43
Freezing Protection 50% dilution with water	°C	-38

*The Above Test Result is subject for change and for reference only

