



600 C2
0W30



German Quality

MUXX OIL GmbH
15 Frankenhauser St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

-Fully Synthetic Passenger Car Motor Oil

-D 600 C2 0W30 is a high performance fuel saving engine oil based on 100% synthetic and PAO technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a ACEA A5/B5 specification is required and suitable for all engines which require an ACEA C2 and PSA B71 2290 performance specification.

-D 600 C2 0W30 is based on high performance PAO (PolyAlphaOlefine) synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

Performance Levels

API SN/CF ACEA A1/B1 ACEA A5/B5 ACEA C2 PSA B71 2290 ILSAC GF-5

Test Item	Typical Spec.	Typical Result
SAE Grade		0W30
Density @15°C	kg/m ³	859
Kin. Viscosity @40°C	mm ² /s	51
Kin. Viscosity @100°C	mm ² /s	9.6
Viscosity Index		165
Viscosity CCS @-30°, max.	cP	6200
Flash Point COC	°C	>201
Pour Point	°C	-42
Total Base Number	mgKOH/g	8.0
Sulphated Ash	%Wt	0.79

*The Above Test Result is subject for change and for reference only



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

