

H**400 CI-4
15W40**

German Quality

MUXX OIL GmbH
 15 Frankenhauser St., 12249 Berlin,
 Germany.
 Office: +49 (0)30 61633942
 Website: www.muxxlube.de
 E-Mail: service@muxxlube.com

Description

-H 400 CI-4 15W40 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

-H 400 CI-4 15W40 is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

Performance Levels

API CI-4 ACEA E7-08 MB 228.3 MTU Type2 MAN 3275
 VOLVO VDS-3 Mack EO-M+ Detroit Diesel 93K215
 Cummins CES 20072/77

Test Item	Typical Spec.	Typical Result
SAE Grade		15W-40
Density @15°C	kg/m ³	880
Kin. Viscosity @40°C	mm ² /s	101
Kin. Viscosity @100°C	mm ² /s	14.0
Viscosity Index		143
Viscosity CCS @-20°, max.	cP	7000
Flash Point COC	°C	201
Pour Point	°C	-39
Total Base Number	mgKOH/g	10.4
Sulphated Ash	%Wt	1.5

*The Above Test Result is subject for change and for reference only



EELQMS
 EUROPEAN ENGINE
 LUBRICANTS QUALITY
 MANAGEMENT SYSTEM

