

MLI



## 600 5W50



MUXX OIL GmbH 15 Frankenhauser St., 12249 Berlin,

Germany.

Office: +49 (0)30 61633942 Website: www.muxxlube.de E-Mail: service@muxxlube.com

## **Description**

- Fully Synthetic Passenger Car Motor Oil
- X 600 5W50 is a high performance motor oil based on 100% synthetic technology with exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines in passenger cars with or without turbocharger, working under severe temperature and load conditions.
- X 600 5W50 is based on high quality synthetic base oil in combination with an unique additive package to ensure the following properties:
- Excellent thermal- and oxidation stability.
- · Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- · Suited for extreme and severe conditions.

## **Performance Levels**

API SN/CF ACEA A3/B4 BMW LL-01

MB 229.3

VW 502.00/505.00

Porsche A40

| Test Item                 | Typical Spec. | Typical Result |
|---------------------------|---------------|----------------|
| SAE Grade                 |               | 5W50           |
| Density @15°C             | kg/m3         | 859            |
| Kin. Viscosity @40°C      | mm2/s         | 110            |
| Kin. Viscosity @100°C     | mm2/s         | 17.8           |
| Viscosity Index           |               | 180            |
| Viscosity CCS @-30°, max. | cР            | 6600           |
| Flash Point COC           | °C            | >201           |
| Pour Point                | °C            | -39            |
| Total Base Number         | mgKOH/g       | 10             |
| Sulphated Ash             | %Wt           | 1.16           |

<sup>\*</sup>The Above Test Result is subject for change and for reference only







